

JABS Group A/S
Kratholmvej 27B
DK,5260 Odense S
Denmark

22

Dop ref. Opt2022-F3

EN 14351-1:2006 + A2:2016
NB 1235

Windows - Type: 3 layer Optima wood

Dedicated for use in residential and public buildings

Resistance to wind load: npd
Watertightness: npd
Dangerous substances: npd
Load bearing capacity of safety devices (reversible window): Pass
Acoustic performance: npd
Thermal transmittance (U-value):
- Window outward opening 1230x1480 mm standard glazing: 0,97
Radiation properties:
- Solar factor (Bg-value): 0,62
- Light transmittance (LTg-value): 0,75
Air permeability: npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70231523
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.



JABS Group A/S
Kratholmvej 27B
DK,5260 Odense S
Denmark

22

Dop ref. Opt2022-F3

EN 14351-1:2006 + A2:2016
NB 1235

External pedestrian doorset - Type: 3 layer Optima wood

Dedicated for use in residential and public buildings

Resistance to wind load: npd
Watertightness: npd
Dangerous substances: npd
Acoustic performance: npd
Thermal transmittance (U-value):
- Door outward opening 1230x2180 mm standard glazing: 1,0
- Panelled door outward opening 1230x2180 mm: 0,70
Radiation properties:
- Solar factor (Bg-value): 0,62
- Light transmittance (LTg-value): 0,75
Air permeability: npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70231523
acc. EN 14351-1:2006+A2:2016, Tabel E.2 note d.

Declaration of Performance


3 layer Optima wood



Rev. Dop Op12022-43

The performance of the product is in conformity with the declared performance.
The declaration of performance is issued under the responsibility of JABS Group A/S.

On behalf of the producer:


Bo Christensen
Managing director

Odense, 2022-04-26

Product type

Windows and external pedestrian doorset

Identification

3 layer Optima wood

Intended use

Dedicated for use in residential and public buildings

Manufacturer

JABS Group A/S, Kratholmvej 27B
DK,5260 Odense S, Denmark
phone +45 70231523, e-mail info@jabsgroup.com

The Assessment and Verification of Constancy of Performance (AVCP):

System 3

Harmonized standard & Notified Body:

EN 14351-1:2006 A2 -2016
Windows and doors - Product standard, Performance characteristics -
Part 1: Windows and external pedestrian doorset

Danish Technological Institute, NB 1235
tested

- Calculation of thermal properties
- Load bearing capacity of safety devices

ITC report 127335
Report 129215

Declared performance:

Resistance to wind load:

npd

Watertightness:

npd

Dangerous substances:

Passed

Load bearing capacity of safety devices (reversible window):

Passed

Acoustic performance:

npd

Thermal transmittance (U-value):

- Window outward opening 1230x1480 mm standard glazing:

0,97

- Door outward opening 1230x2180 mm standard glazing:

1,0

- Panelled door outward opening 1230x2180 mm:

0,70

Radiation properties:

- Solar factor (gg-value):

0,62

- Light transmittance (LTg-value):

0,75

Air permeability:

npd